

**GRAPHICS** - INK-JET DIGITAL

 Issue date : 07/09/2015  
 Date last modification : 09/01/2017

**4-GL3B-08824 RI-JET 100 GLOSS CLEAR AVM REMOVABLE WKPE140 AIRFLOW**
**Face Material**

Gloss clear monomeric vinyl film.

Type	Monomeric vinyl	
Colour and Finish	Gloss clear	
Weight	134 g/m <sup>2</sup> ±10%	ISO-536
Thickness	100 μ ±10%	ISO 534-80

**Adhesive**

Removable adhesive offering easy and clean removability from glass and from many other substrates. Not recommended on paper, PVC, ABS, PS, air dried paints and varnishes.

Reference	AVM removable	
Type	Acrylic removable	
Min. Appl. Temp.	+10°C	
Service Temp.	-40°C/+100°C	
Shear	High	
Tack	4 N/inch <sup>2</sup>	
Final Adhesion	3 N/inch	

**Liner**

Type	Siliconised two side PE kraft airflow	
Colour and Finish	White	
Weight	144 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	155 μ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

**Applications**

Glass, panels, simple surfaces can be decorated using the Airflow technology and at the same time the decorations can be removed without problems, thanks to the removable adhesive that allows to easily recover the original surface in a very short time and without traces of adhesive.

**Printing Methods**

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

**Shelf life**

 24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

