



Vipond's Paints Pty Ltd

2 Norris Street North Coburg 3058
Phone (03) 93504188 Fax (03) 93542732
Email vic@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

FLUORESCENT PAINT

Description

A water thinned acrylic paint using the highest quality pigment available for colour brightness and colour retention. Fluorescent paint is inherently transparent which allows light to travel through the paint film and then re-emit light of its own colour, under "black light" it glows very brightly. To enable this to happen it must be applied over a white background. Due to this characteristic fluorescent paint has poor light stability and will begin to fade within 6 months when subjected to direct sunlight.

Use

It is primarily used for signwriting windows and buildings, where the brilliance of fluorescent colour is required. This product can also be used to paint vinyl banners.

Application

Thoroughly stir and apply by brush, roller or spray. Apply 2 coats for coverage and durability.

Surface Preparation

Thoroughly clean the surface. Then apply Viponds Background White. Use Vipond's Super Lustre White for banner applications. It **must** be applied over a white background.

Drying

Under normal drying conditions (above 15°C and low humidity) it is touch dry within 30 minutes and can be recoated after 2 hours.

Cleaning up and thinning

Use clean water only

Coverage

Approximately 14 square metres per litre per coat

Pack Size

500 mls, 1 litre, 4 litre.

Colours

White/clear, yellow, green, pink, red, orange, blue, purple

Revised July 2005