



## Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email [info@viponds.com.au](mailto:info@viponds.com.au)

[www.viponds.com.au](http://www.viponds.com.au)

## PRODUCT INFORMATION

### ACRYLIC GLOSS

#### Description

A 100% acrylic water thinned paint that dries to a glossy durable finish and is available in white, pastel and deep accent tones. Suitable for exterior and some interior surfaces.

#### Use

The product has excellent opacity using the most light fast pigments for exterior use. Suitable on a variety of substrates such as brick, metal, cement render, masonry, plaster board and timber. It has excellent durability for all exterior services for the home, commercial and industrial premises. It is the ideal product for sign, display and mural work. When an anti graffiti coating is to be applied over the top it is recommended to use Viponds Ecoshield or Low Sheen exterior. When a glossy paint is required for internal use, Viponds Acrylic Trim or Ecoshield is recommended.

#### Application

Brush, roll or spray. Apply two coats for durability and for a perfect finish.

#### Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

**Timber** – Sand, dust down and apply a coat of wood primer. Fill holes with filler.

**Galvanised Iron and Aluminium** – Remove oil and grease. Apply Acrylic metal primer.

**Iron and steel** – Remove oil, grease and rust. Treat remaining rust with a rust converter then apply acrylic metal primer.

**Brick and Masonry** – Remove all loose and powdery material with a stiff brush and wash down. No primer required unless to assist with coverage of an accent colour. Use Viponds Multi Purpose undercoat.

**Previously painted** – Scrape off all loose and flaking paint and sand glossy surfaces. Wash down with sugar soap. Spot prime bare wood and metal with appropriate primer. An adhesion test may be required. When using deep tone colours such as Lemon Yellow and VIP Red apply a white or light grey undercoat. This will ensure true colour and help coverage.

**Drying**

Under Normal drying conditions (above 15°C and low humidity) it will be touch dry in 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C. Where the product is drying too quickly for application purposes then Viponds Hot Weather thinner is recommended

**Clean up and Thinning**

Use clean water only.

Thin with Viponds Hot Weather thinner

**Coverage**

14 - 16 square metres per litre per coat.

**Pack Size**

500 mls, 1 litre, 4 litre and 10 litres

**Colours**

Colour card, pantone colours , RAL colours and customer specifications.

Revised January 2021