



HP Latex 315 Print and Cut Solution

Grow—with this 54-inch business-ready print and cut solution



Your perfect fit

- Do more apps—cut through stickers, customizable clothing, window graphics; reach indoor spaces solvent can't
- With HP Signage Suite in the box, no design skills are needed—bring your ideas to life in 3 simple steps¹
- Space is not the limit—HP print and cut uses essentially the same operating space as an integrated device²

True print and cut

- Print AND cut at the same time—versus print OR cut with solvent—with this reliable, dual-device solution
- Avoid solvent wait time—prints come out dry, cut/laminate right away; no need to laminate short-term jobs³
- Print longer runs with reliable, high-precision cutting—high-accuracy Optical Positioning System (OPOS)

Reliable, integrated workflow

- Print and cut in 5 simple steps—includes in-box HP FlexiPRINT and CUT RIP and friendly user interface
- One point workflow management—edit/print jobs, including HP Barcode unattended cutting, without interruption
- Avoid the complexity of other dual-devices—the complete HP solution is designed to work as one

For more information, please visit
hp.com/go/Latex315printandcut

Join the community, find tools, and talk to experts.
Visit the HP Latex Knowledge Center at
hp.com/communities/LKC

¹ Requires an HP Applications Center account, Internet connection, and connected Internet-capable device. For more information, see hpapplicationscenter.com.

² Based on operating area requirements, the HP dual-device print and cut solution requires less than 1 m² of additional space compared to integrated solvent-technology based print and cut solutions in the market as of February, 2017.

³ You can consider unlaminated use for short-term signage with scratch resistance comparable to hard-solvent inks on self-adhesive vinyl and PVC banner. Scratch-resistance comparison based on testing third-generation HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.

Technical specifications

HP Latex 315 Printer



Printing	Printing modes	48 m ² /hr (517 ft ² /hr) - Billboard (2 pass) 16 m ² /hr (174 ft ² /hr) - Outdoor Plus (6 pass) 12 m ² /hr (129 ft ² /hr) - Indoor Quality (8 pass) 10 m ² /hr (108 ft ² /hr) - Indoor High Quality (10 pass) 6 m ² /hr (65 ft ² /hr) - Backlits, Textiles, and Canvas (16 pass) 5 m ² /hr (54 ft ² /hr) - High Saturation Textiles (20 pass)	
	Print resolution	Up to 1200 x 1200 dpi	
	Margins	5 x 5 x 5 mm (0.2 x 0.2 x 0.2 in)	
	Ink types	HP Latex Inks	
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer	
	Cartridge size	775 ml	
	Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)	
	Color consistency ⁴	Average ≤ 1 dE2000, 95% of colors ≤ 2 dE2000	
	Media	Handling	Roll feed; take-up reel (optional); automatic cutter (for vinyl, paper-based media, backlit polyester film)
		Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles and any other porous materials require a liner)
Roll size		254 to 1371-mm (10 to 54-in) rolls (580 to 1371-mm (23 to 54-in) rolls with full support)	
Roll weight		25 kg (55 lb)	
Roll diameter		180 mm (7.1 in)	
Applications	Thickness	Up to 0.5 mm (19.7 mil)	
	Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics		
	Connectivity	Interfaces (standard) Gigabit Ethernet (1000Base-T)	
Dimensions (w x d x h)	Printer	2307 x 840 x 1380 mm (91 x 33 x 54 in)	
	Printer (shipping)	2541 x 760 x 1250 mm (100.1 x 30 x 49.3 in)	
Weight	Printer	174 kg (384 lb)	
	Printer (shipping)	257.5 kg (568 lb)	
What's in the box	HP Latex 315 Printer, printheads, maintenance cartridge, printer stand, spindle, user maintenance kit, edge holders, quick reference guide, setup poster, power cords		
Environmental ranges	Operating temperature	15 to 30°C (59 to 86°F)	
	Operating humidity	20 to 80% RH (non-condensing)	
Acoustic	Sound pressure	54 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep)	
	Sound power	7.2 B(A) (printing); 5.5 B(A) (ready); < 3.5 B(A) (sleep)	
Power	Consumption	2.2 kW (printing); 70 watts (ready); < 2.5 watts (sleep)	
	Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 3 A max per printer power cord; 13 A max per curing power cord	
Certification	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)	
	Environmental	ENERGY STAR, WEEE, RoHS (EU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT Bronze, OSHA, CE marking compliant	
Warranty	One-year limited hardware warranty		

HP Latex 54 Cutter

Cutting	Cut type	Drag-knife with TurboCut and Tangential emulsion modes	
	Cut width	135 cm (53.1 in)	
	Cut speed	Up to 113 cm/sec (44 in/sec) diagonal	
	Acceleration	Up to 3 G diagonal	
	Accuracy	0.2% of movement or 0.25 mm, (0.01 in) whichever is greater	
	Repeatability	±0.1 mm (0.004 in)	
	Cut force	0 to 400 grams of downforce, in 5-gram steps	
	Cut thickness	0.05 to 0.25 mm (0.002 to 0.01 in); 0.8 mm (0.03 in) with optional sandblast blade	

Connectivity	Interfaces (standard)	USB and Ethernet (LAN)
Dimensions (w x d x h)	Cutter	1750 x 680 x 1145 mm (68.9 x 26.8 x 45.1 in)
	Cutter (shipping)	1880 x 480 x 670 mm (74 x 18.9 x 26.4 in)
Weight	Cutter	48 kg (106 lb)
	Cutter (shipping)	69 kg (152 lb)
What's in the box	HP Latex 54 Cutter, cutter stand, HP FlexiPrint and Cut RIP, HP Cutter Control software, quick reference guide, setup poster, documentation software, power cords, standard holder (1), standard blades (2), cut-off knife (1), 3-in media flanges (set of 2)	
Warranty	One year, after the HP Latex End of Installation Registration is completed by an HP authorized reseller	

Ordering information

Product	1LH38A	HP Latex 315 Print and Cut Solution	
Accessories	1UP26A	HP Latex Cutter Extended Kit	
	1UP27A	HP Latex 2-in Media Holder Kit	
	1UX44A	HP Latex Standard Blade Kit	
	1UX45A	HP Latex Specialty Blade Kit	
	F0M55A	HP Latex 54-in Printer 2-in Spindle	
	F0M59A	HP Latex 300/500 User Maintenance Kit	
	WSA60A	HP Latex 300 54-in Take-Up Reel	
	Original HP printheads	CZ677A	HP 831 Cyan/Black Latex Printhead
		CZ678A	HP 831 Yellow/Magenta Latex Printhead
		CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead
CZ680A		HP 831 Latex Optimizer Printhead	
Original HP ink cartridges and maintenance supplies		CZ688A	HP 831B 775-ml Black Latex Ink Cartridge
	CZ689A	HP 831B 775-ml Cyan Latex Ink Cartridge	
	CZ690A	HP 831B 775-ml Magenta Latex Ink Cartridge	
	CZ691A	HP 831B 775-ml Yellow Latex Ink Cartridge	
	CZ692A	HP 831B 775-ml Light Cyan Latex Ink Cartridge	
	CZ693A	HP 831B 775-ml Light Magenta Latex Ink Cartridge	
	CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge	
	CZ681A	HP 831 Latex Maintenance Cartridge	
	Original HP large format printing materials	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.	
		HP Permanent Gloss Adhesive Vinyl REACH ⁵	
HP Backlit Polyester Film  ⁶			
HP PVC-free Durable Smooth Wall Paper REACH, ⁵ FSC [®] certified, ⁷ UL GREENGUARD GOLD Certified ⁸			
HP Premium Poster Paper  ⁶ FSC [®] certified ⁷			
For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com .			
Service and support		U9PN0E	HP 2 year Next Business Day with Defective Media Retention Print&Cut Latex 315 HW Support
		U9PN1E	HP 3 year Next Business Day with Defective Media Retention Print&Cut Latex 315 HW Support
		U9PN4PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention Print&Cut Latex 315 HW Support
		U9PN5PE	HP 2 year Post Warranty Next Business Day with Defective Media Retention Print&Cut Latex 315 HW Support


⁴ The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) ≤ 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

⁵ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP.Printing.Products.and.Consumable.Supplies.


⁶ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.

⁷ BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions.


⁸ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.




PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. KEY SPECIFIC ATTRIBUTES EVALUATED: UL 2801




PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS. UL.COM/GGG. UL 2818. GOLD




Eco Mark Certification
Number 14142007



ENERGY STAR



CE



EPEAT
BRONZE

NOTE: Some certifications may only apply to the printer

