

Product Description

Metamark MDiG features the MetaGlide® next generation air release system offering improved all round handling. With its micro structured air release liner, lift and reapply MetaGlide® graphics with a smooth clean peel that prevents damage to the graphic. MetaGlide® system offers exceptional layflat printability. Prints can stay stored or loosely rolled confidently without tunnelling or delamination. Metamark's 70 micron white face film with its distinctive coating technology produces outstanding print performance on Solvent, Eco Solvent, UV and Latex printers.

Printing and Handling

- Suitable for use on Solvent, Eco Solvent, Latex and U.V. inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

Overlaminating

- Overlaminating is recommended to prevent abrasion and to extend colour fastness.
- Allow the inks to cure before overlaminating, this is usually 24-48 hours.
- The matched laminate for MDiG is MetaGuard MGi. For all other laminates the user should determine suitability.

Application

- Allow the inks to cure before cutting flush to the print, this is usually 24-48 hours. Suitable for dry application only.
- Apply to flat surfaces or simple curves. Apply unstressed. Not suitable for application over rivets or into deep recesses.
- Not recommended for use on low energy surfaces such as polypropylene. The user should determine suitability of substrate.
- Refer to www.metamark.co.uk for application guidelines.

Face Film

| | |
|---------------------|--------------------------------|
| Face Film: | Polymeric Calendered PVC |
| Gauge: | 70 micron nominal |
| Tensile Strength | 49N/25mm MD / 47N/25mm TD nom. |
| Elongation at break | 180% MD nominal |

Adhesive

| | |
|---------------------------|--|
| Type | MetaGlide® Air Release Permanent Solvent-Based Adhesive. |
| Weight | 19gsm nominal |
| Adhesion to glass 20 mins | 10N/25mm nominal |
| Adhesion to glass 24 hour | 20N/25mm nominal |
| Perceived tack | Medium |
| Application temperature | +5°C to +60°C |
| Service temperature | -30°C to +110°C |

Release Liner

| | |
|--------|--|
| Print | 'MetaGlide®' purple print |
| Weight | 140 gsm nominal |
| Type | Structured layflat kraft paper with PE coating |

Finishes

| | | |
|--------------------|----------|-------------|
| Finishes Available | MDiG-100 | White Gloss |
|--------------------|----------|-------------|

Roll Presentation

| | |
|--------------|---|
| Roll sizes | 760mm x 25m / 50m 1370mm x 25m / 50m 1600mm x 25m / 50m |
| Presentation | Face film outwards, on a 76mm core. |

Durability

| | |
|-----------------------|---|
| Shelf Life | 2 years |
| External weathering | 5 years (International customers please contact your local Metamark partner for confirmation of durability). This refers to the unprinted vinyl. Refer to ink manufacturer for durability of the finished product. |
| Fire Rating | Class B. BS EN 13501-1:2007 |
| Dimensional Stability | <0.4mm (48h at 70°C on aluminium) |
| Chemical Resistance | The unprinted film is resistant to mineral oils, fats and fuels, aliphatic solvents, mild acids, salt and alkali for e.g. diesel oil, gasoline, paraffin, hydraulic oil, antifreeze, soap suds, etc. |
| Regulations | REACH and RoHS compliant |

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

○ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147

○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

sales@metamark.co.uk
www.metamark.co.uk