

## Prepasted WallpaperSol Persomural 225

### ■ satin 3258 - 225 g/m<sup>2</sup>

High quality wallpaper coated with a satin finish specifically for solvent inks, providing outstanding colour brilliance and scratch resistance. Thanks to the paste back coating, activated by wetting it with water, it can be hung with no additional protection needed.

#### Applications

- Interior design

#### Advantages

- Backcoated with a permanent waterbased paste guaranting long-lasting use
- High opacity for good coverage, covering small hairline cracks
- PVC-free and FSC certified
- Quick dry
- Wide colour gamut and good colour reproduction
- The inkjet coating has a smooth surface with satin finish
- Both coating and print are water-resistant – no liquid lamination required
- High dimensional stability and wet strength, allowing “pre & post” paste cutting

## Prepasted WallpaperSol Persomural 225

■ satin 3258 - 225 g/m<sup>2</sup>

### List of Printers

Printer	Ink	Quality
Hewlett Packard DJ L65500 Latex ink	IR Curing / Latex Ink	Good
Hewlett Packard DJ L25500 / 26500 / 28500 Latex ink	IR Curing / Latex Ink	Good
ColorSpan DisplayMaker 72S	Eco Solvent	Excellent
ColorSpan Display Maker 72 UVR	UV Curable Ink	Excellent
Epson Stylus Pro GS6000 UltraChrome GS	Eco Solvent	Excellent
Roland SolJet SJ540 / SC540 SJ 740 / SC740	Eco Solvent	Excellent
Roland SC-500 Permasol S	Solvent Ink	Excellent
Roland VersaCAMM SP-300i / SP-540i	Eco Solvent	Excellent
Roland VS 540 / VS 640	Eco Solvent	Excellent
Roland CJV 30	Eco Solvent	Excellent

Last update: 12.02.2013

## Prepasted WallpaperSol Persomural 225

■ satin 3258 - 225 g/m<sup>2</sup>

### Physical Properties

Total weight	225 g/m <sup>2</sup>	ISO 536
Thickness	330 µm	ISO 534
Whiteness	70	CIE
Opacity	91 %	ISO 2471
Colour (D50 2°)	L* 96 a* -0.3 b* 3	ISO 13655

### Recommended use and storage

To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

The values provided on this datasheet are only for orientation.

Before using our media please check its compatibility for your printer and intended application. Technical specifications are subject to change, therefore we do not take responsibility for any misprints resulting from technically modified inks and/ or printers. 04.06.2012