



## TRANSPARENT GLITTER FILMS STYLETECH™ 4000TG Series 3Mil Specialty Vinyl

Styletech Transparent Glitter Films can be easily cut and applied allowing you to turn any flat glass surface into a work of art. You can add color and privacy, creating an entirely new environment of light, space, dimension and visual effects.

**TYPICAL PHYSICAL PROPERTIES:** 3.2 mil calendered transparent film with permanent acrylic adhesive.

**A. PHYSICAL PROPERTIES:**

PVC Film Thickness (mils)	3.2
PSA Thickness (mils)	1.0
Liner (weight)	78 lbs.
Tensile strength (lbs/in. break load)	8-10
Elongation	50% - 100%

**B. ADHESION PROPERTIES:**

	<b>oz/in.</b>
PSTC-1 (Instant R.T.)	40
PSTC (1 hr. R.T.) Stainless Steel	55
PSTC (24 hr. R.T.) Stainless Steel	60
PSTC (72 hr. R.T.) Stainless Steel	65

**C. RESISTANCE:** Resistance to mild alkalis and acids, most petroleum based greases, oils and salt spray.

**D. SERVICE TEMPERATURE:** 60°F - 200°F

**E. HEAT SHRINKAGE** (24 hr. at 150°F): .01

**F. SHELF LIFE** (Stored under 73°F and 50% relative humidity): 1 Year

**G. OUTDOOR DURABILITY** (When properly converted and applied, vertical exposure, non-printed): Up to 5 Years

**NOTE:** All information based on tests believed to be reliable. These values do not constitute guaranty and do not constitute a warranty. Purchaser is to independently determine suitability of this material for specific purpose.